

6AYEM-GT

L-rating 670kW (911mhp)
S-rating 737kW (1002mhp), 749kW (1018mhp)



- Common Rail system
- 6-cylinder, direct injection, heat exchanger cooling.
- Turbocharger + intercooler.
- 4-valves per cylinder for higher combustion efficiency.
- Available either with marine gear or without marine gear.
- Conform to IMO Tier II emissions regulations.

Specifications


Model	6AYEM-WGT	
Number of cylinders	6 in-line	
Bore × stroke	mm	155 × 180
Displacement	lit.	20.379
Rated output	kW(hp)/rpm	L : 670(911)/1938, S : 737(1002)/2000, S : 749(1018)/2000
Combustion system	Direct injection	
Aspiration	Turbocharger + intercooler	
Starting system	Electric starting motor (24V 8.0kW)	
Cooling system	Heat exchanger	
Size of flywheel housing and flywheel	SAE #0 and 18 in.	
Dry mass	kg	2418 (without marine gear)
Dimensions (L×W×H)	mm	2000×1305×1531

Marine gear specifications


Engine model : 6AYM-WGT	
Model	YXH-240-7
Type	Hydraulic multi-disc clutch
Reduction ratio (Ahead)	1.95 2.27 2.56 3.03 348
Direction of rotation (propeller shaft)	Clockwise or counterclockwise
Dry weight	kg 632

Dimensions Unit:mm


Engine only / Front view




Engine only / Right side view (Shallow sump)



With YXH240 gearbox / Rear view



With YXH240 gearbox / Right side view



— Marine gear

Performance curves

